



## SPECIFICATIONS AND TECHNICAL DATA

|                                  |                                 |                                 |
|----------------------------------|---------------------------------|---------------------------------|
| Chemprene Specification          |                                 | • 6603(18)(69-1).010            |
| Color                            |                                 | • White                         |
| Plies                            |                                 | • 3                             |
| Weight                           | lbs/Sq ft<br>kgs/m <sup>2</sup> | • 1.09<br>• 5.32                |
| Available Widths                 | in<br>Mm                        | • 72<br>• 1829                  |
| Overall Gauge                    | in<br>mm                        | • .250 ±.025<br>• 6.35±.51      |
| Recommended working tension      | lbs/in<br>N/mm                  | • 150<br>• 26.8                 |
| Minimum pulley diameter          | in<br>mm                        | • 2<br>• 50.8                   |
| Temperature range                | F.<br>C.                        | • 0° to 250°<br>• - 18° to 121° |
| Meets FDA                        |                                 | • Yes                           |
| Compound                         |                                 | • NBR                           |
| Cover Surface                    |                                 | • Meatecleat                    |
| Bottom Surface                   |                                 | • Friction                      |
|                                  |                                 |                                 |
|                                  |                                 |                                 |
| Coefficient of friction<br>Steel | Cover<br>Bottom                 | 1.0<br>0.3                      |