

**Call:** (800) 230-37189

**Fax:** (800) 677-27063

**Email:** [sales@anametelectrical.com](mailto:sales@anametelectrical.com)

**Website:** [www.anacondasealtite.com](http://www.anacondasealtite.com)

## Type UI - Capillary Armor Stainless Steel Stripwound Hose

### Construction

- Constructed of continuously interlocked Type 302 stainless steel core for exceptional crush and corrosion resistance.
- Product will not spring open or unwind.
- Extruded PVC, Silicone, PTFE, and Thermoplastic Rubber jackets available upon request.
- Available in brass, galvanized steel and aluminum.

### Certification

RoHS WEEE COMPLIANT



1

<u>Item #</u>	<u>Nominal Size</u>	<u>Length</u>	<u>Packaging</u>	<u>Inside Diameter</u>	<u>Outside Diameter</u>
<a href="#"><u>451550-0070</u></a>	5/32 in 4 mm	1000 ft 304.8 m	Standard Reels	0.160 to 0.175 in 4.064 to 4.445 mm	0.255 to 0.270 in 6.477 to 6.858 mm
<a href="#"><u>451554-0070</u></a>	3/16 in 5 mm	1000 ft 304.8 m	Standard Reels	0.180 to 0.195 in 4.572 to 4.953 mm	0.275 to 0.290 in 6.985 to 7.366 mm
<a href="#"><u>451560-0070</u></a>	7/32 in 5.5 mm	1500 ft 457.2 m	Standard Reels	0.215 to 0.230 in 5.461 to 5.842 mm	0.310 to 0.325 in 7.874 to 8.255 mm

<u>Item #</u>	<u>Nominal Size</u>	<u>Length</u>	<u>Packaging</u>	<u>Inside Diameter</u>	<u>Outside Diameter</u>
<u>451564-0070</u>	1/4 in 6 mm	800 ft 243.84 m	Standard Reels	0.245 to 0.260 in 6.223 to 6.604 mm	0.340 to 0.355 in 8.636 to 9.017 mm
<u>451568-0070</u>	5/16 in 8 mm	500 ft 152.4 m	Standard Reels	0.310 to 0.325 in 7.874 to 8.255 mm	0.405 to 0.420 in 10.287 to 10.668 mm
<u>451572-0070</u>	3/8 in 9.5 mm	500 ft 152.4 m	Standard Reels	0.370 to 0.390 in 9.398 to 9.906 mm	0.485 to 0.505 in 12.319 to 12.827 mm
<u>451574-0070</u>	7/16 in 11 mm	500 ft 152.4 m	Standard Reels	0.432 to 0.452 in 10.973 to 11.481 mm	0.547 to 0.567 in 13.894 to 14.402 mm
<u>451576-0070</u>	1/2 in 12.7 mm	500 ft 152.4 m	Standard Reels	0.495 to 0.515 in 12.573 to 13.081 mm	0.610 to 0.630 in 15.494 to 16.002 mm